

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other Instructions on re-
verse side)Form approved.
Budget Bureau No. 42 B1424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
2. NAME OF OPERATOR Brazos Petroleum Company	7. UNIT AGREEMENT NAME
3. ADDRESS OF OPERATOR 708 Petroleum Bldg. - Midland, Texas 79701	8. FARM OR LEASE NAME Holcomb '18' Federal
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FNL & 1980' FEL, Section 18, T-9-S R-38-E	9. WELL NO. 2
	10. FIELD AND POOL, OR WILDCAT Sawyer (San Andres)
	11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA Sec. 18, T-9-S, R-38-E
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3953 GR
	12. COUNTY OR PARISH Lea
	13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	FULL OR ALTER CASING
FRACTURE TREAT	MULTIPLE COMPLETE
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANS
(Other)	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	RELANDING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other) Set casing	

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-17-81 Ran 4-1/2" bottom-to-top as follows:

Float shoe with latch down assembly	1.69'
49 jts. 4-1/2" 10.5# J55 ST&C casing	2073.23'
Pengo Selective Cement Stage Tool	2.22'
73 jts. 4-1/2" 10.5# J55 ST&C casing	2988.89'
122 jts.	5066.03'
Top of casing collar above KB	-1.03'
Casing set @ KDB datum	5065.00'

Cemented with 225 sx 50:50 "C" poz. with 8# salt per sack & 1/4 flocele per sack, plug down @ 1:45 AM 1-17-81. Float held OK, set slips on 4-1/2" casing. Cut off 4-1/2" csg.

RECEIVED
JAN 21 1981U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Walter BrownTITLE Production ClerkDATE 1-20-81

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

ACCEPTED FOR RECORD
DATE

JAN 21 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO