DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE LC 068035 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas	Holcomb "18" Federal
well well tother	9. WELL NO.
2. NAME OF OPERATOR	1
Brazos etroleum Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Sawyer (San Andres)
P.O. Box 1782 - Midland, Texas 79702	11. SEC., T., R., M., OR BLK. AND SURVEY OF AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Sec. 18 - T-9-S, R-38-E
below.) AT SURFACE: 1980' FWL & 760' FNL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same	Lea New Mexico
AT TOTAL DEPTH: Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3976 GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL	(NOTE) Report results of multiple completion or zon
PULL OR ALTER CASING	
ABANDON* Oil & G. U.S. GEOLOGIC	
(other) Gas Separator Installed ROSWELL, NEW	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-12-82 Installed gas separator - first gas sales on No. 1 well thru new meter 1-7-82. All to be commingled & prorated by monthly test.

after metering

____ Set @ _____ Ft. Subsurface Safety Valve: Manu. and Type _ 18. I hereby certify that the foregoing is true and correct TITLE Production Secretarine _ SIGNED_ ACCEPTED FOR RECORD space for Federal or State office use) _____ DATE _ PETER W. CHESTER APPROVED BY CONDITIONS OF APPROVAL, IF ANY: FEB 26 1982 U.S. GEOLOGICAL SURVEY

ROSWELL, NEW MEXICO *See Instructions on Reverse Side