

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLIC
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-4424

5. LEASE DESIGNATION AND SERIAL NO.

LC 068035

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT ASSIGNMENT NAME

8. FARM OR LEASE NAME

Holcomb '18' Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Sawyer (San Andres)

11. SEC., T., R., M., OR PLK. AND
SURVEY OR AREA

Sec. 18-T-9-S, R-38-E

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Brazos Petroleum Company

3. ADDRESS OF OPERATOR

708 Petroleum Bldg. - Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface
1980' FWL & 760' PNL, Sec. 18
T-9-S, R-38-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DE, RT, GR, etc.)

3976 GR

12. COUNTY OR PARISH

Lea

13. STATE

N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) Set casing ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL ☐

ALTERING CASING ☐


ABANDONMENT* ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-9-81 Ran 4-1/2" bottom-to-top as follows:

4-1/2" (Halliburton) Float shoe w/latch down assembly	1.80'
52 jts. 4-1/2" 10.5# K55 ST&C casing	2039.10'
4-1/2" (Pengo) Selective Stage cementing tool	2.50'
77 jts. 4-1/2" 10.5# K55 ST&C casing	3023.54'
Total casing	5066.94'
Total of top of casing to KB	-1.94'
Csg. set depth KB datum	5065.'

Ran casing with 8 centralizers, cemented w/225 sx
50:50 Poz "C" w/8# salt per sack & 1/4# flocele
per sack. Nippled down B.O.P., set slips on 4-1/2"
csg., cut off 4-1/2" casing.



U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Vance Brown

TITLE Production Clerk

DATE 1-13-81

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

ACCEPTED FOR RECORD

68
JAN 14 1981

DATE _____

U.S. GEOLOGICAL SURVEY

*See Instructions on Reverse Side