Form 9-331

COPY TO O. C. C

UNI D STATES

SUBMIT IN TRIPL.	E*	
(Other instructions	re-	

Form approved.

(31 :	DCPART	5. LEASE DESIGNATION AND SERIAL NO. LC 068035			
		TICES AND REPORTS osals to drill or to deepen or plus CATION FOR PERMIT—" for such		6. IF INDIAN, ALLOT	TEE OR TRIBE NAME
1.	OIL GAS X OTHER		MAY 2 3 1 2 2 1	7. UNIT AGREEMENT	NAME
2.	NAME OF OPERATOR		randra nta ti (A) ar i bergani i i i i i i i i i	8. FARM OR LEASE 1	NAME
	Brazos Petroleum	Company	HS Area	Holcomb '	18'Federal
3.	ADDRESS OF OPERATOR			9. WELL NO.	
	708 Petroleum Bld	g Midland,Texa	as 79701	1	
4.	LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface		10. FIELD AND POOL, OR WILDCAT		
	1980' FWL & 760' FNL, Sec. 18				
	T-9-S, R		J. 10	SURVEY OR AL	REA
	1-9-5, K	- 20-12		Sec. 18,T-	-9-S,R-38-E
14.	PERMIT NO.	15. ELEVATIONS (Show whether	DF, RT, GR. etc.)	12. COUNTY OR PAR	ISH 13. STATE
		3976'		Lea	N.M.
16.	Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data				
NOTICE OF INTENTION TO:			ENT REPORT OF:		
	TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRIN	O WELL
	FRACTURE TREAT	MULTIPLE COMPLETE	Holcomb '18' Federal 9. WELL NO. 1 10. FIELD AND POOL, OR WILDCAT Sawyer (San Andres) 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 18, T-9-S, R-38-E DF, RT, CR, etc.) 12. COUNTY OR PARISH 13. STATE Lea N.M. Nature of Notice, Report, or Other Data SUBSEQUENT REPORT OF:		
	SHOOT OR ACIDIZE	ABANDON®		_	MENT*
	REPAIR WELL	CHANGE PLANS	(Other)		
	(Other) (Note: Report results Completion or Recompl		of multiple completion on Well etlon Report and Log form,)		
17.	DESCRIBE PROPOSED OR COMPLETED OF proposed work. If well is direct nent to this work.) •	PERATIONS (Clearly state all perti- tionally drilled, give subsurface lo	nent details, and give pertinent dates, ocations and measured and true vertice	including estimated il depths for all mark	date of starting any kers and zones perti-

1-2-81 M.I. & R.U. Norton Drlg. Co. Drlg. 12-1/4" hole. Drld. to 420' P.O.H., ran 10 jts. 430' 8-5/8" 24# J55 ST&C casing set @ 420'. Cemented with 275 sks. Class "C" with 2% CaCl 2 & 1/4# Flocele per sack. Circulated an estimated 60 sks. cement to surface. Plug down @ 10:15 PM 1-1-81

SIGNED	TITLE Production Clerk	DATE 5-22-81
ACCEPTED FOR RECORD	TITLE	DATE
U.S. GEOLOGICAL SURVEY	*See Instructions on Reverse Side	