

NO. OF COPIES RECEIVED	
DISTRIBUTION	
ALTA FE	
FILE	
J.S.G.S.	
AND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-85

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
V-17

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> <small>DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.</small>	
OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
Name of Operator	8. Farm or Lease Name
Southern Union Expl. Co. of TX	Susco 36 State
Address of Operator	9. Well No.
1217 Main St, Texas Federal Bldg, Suite 400, Dallas, TX 75202	1
Location of Well	10. Field and Pool, or Warrant
UNIT LETTER M 660 FEET FROM THE S LINE AND 660 FEET FROM THE W LINE, SECTION 36 TOWNSHIP 10-S RANGE 33-E N.M.P.M.	Inbe Perma Penn
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
4195.3' GR	Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Place a 50' cement plug in the 5½" casing above the open perforations at 3551'-55'.
- Try to retrieve 3000' of 5½" casing.
- Place a 50' cement plug inside and out of the top of the 5½" stub.
- Place a 100' cement plug above the salt section at 1980'.
- Place a 10 sack plug at the surface.

A verbal approval for the above proposal was given to SX field foreman Alvin Wilks by Jerry Sexton on 7/29/81.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Pat M. Donnell TITLE Drilling & Production Engineer DATE 8/3/81

APPROVED BY Jerry Sexton TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
 CONDITIONS OF APPROVAL, IF ANY: