

UNITED STATES RECEIVED  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a well. Plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐  
2. NAME OF OPERATOR  
Brazos Petroleum Company  
3. ADDRESS OF OPERATOR  
P. O. Box 1782 Midland, Texas 79702  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE:  
AT TOP PROD. INTERVAL: 660's/1980'W  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	TEST WATER SHUT-OFF	FRACTURE TREAT	SHOOT OR ACIDIZE	REPAIR WELL	PULL OR ALTER CASING	MULTIPLE COMPLETE	CHANGE ZONES	ABANDON*	(other)
	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	

SUBSEQUENT REPORT OF:

5. LEASE  
NM-28064  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
Ferderber  
8. FARM OR LEASE NAME  
Ferderber Federal  
9. WELL NO.  
1  
10. FIELD OR WILDCAT NAME  
Sawyer (San Andres) Assoc.  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 7, T-9-S, R-38-E  
12. COUNTY OR PARISH  
Lea  
13. STATE  
NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3972.3'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

CASING RECORD

8 5/8 set @ 433' w/250 sx. circulated to surface  
4 1/2 set @ 5060' w/700 sx. Class "C" & 300 sx. 50:50 POZ circulated to surface.  
PERFORATIONS  
4858'-4992' SJS

PLUGGING RECORD

Circulated well w/10# mud laden fluid - spot 35 sx plug thru tbg. @ 5000' 4800' [Tagged]  
Pull tbg to 483' - spot 15 sx plug @ 483'-383', POOH tag plug - run 50' of tbg.  
and spot 10 sx plug to surface.  
All plugs to be spotted w/10# mud laden fluid.  
Proceedure verbally approved by Shannon Shaw 12/1/87  
work commenced on 12/2/87

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Robert H. Oden TITLE agent DATE 12/2/87

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: