

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG-362	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Brazos Petroleum Company		8. Farm or Lease Name Getty State
3. Address of Operator 708 Petroleum Bldg. - Midland, Texas 79701		9. Well No. 2
4. Location of Well UNIT LETTER <u>A</u> <u>760</u> FEET FROM THE <u>North</u> LINE AND <u>660'</u> FEET FROM THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>9-S</u> RANGE <u>37-E</u> NMPM.		10. Field and Pool, or Wildcat Sawyer (San Andres)
15. Elevation (Show whether DF, RT, GR, etc.) 3943.3 GL		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-15-81 Spudded @ 3:30 P.M. Ran 10 jts 8 5/8" 24# K55 ST&C csg with guide shoe & 2 centralizers, csg set @ 435', cemented with 250 sxs Class "C" cement with 1/4 # flocele per sack & 27. CaCl₂ plug down @ 11:15 PM. circulated on estimated 45 sx cement to surface, WOC & NU BOP.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Candice R. Farr TITLE Production Clerk DATE 6-17-81

APPROVED BY [Signature] TITLE [Signature] DATE JUN 19 1981

CONDITIONS OF APPROVAL, IF ANY: