

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well      gas ☒ well      other ☐

2. NAME OF OPERATOR  
Brazos Petroleum Company

3. ADDRESS OF OPERATOR  
P.O. Box 1782 - Midland, Texas 79702


4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL & 660' FEL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☒ XX

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐



OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

5. LEASE  
LC 063623

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Kringel Federal

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Sawyer (San Andres)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 31, T-9-S, R-38-E

12. COUNTY OR PARISH  
Lea

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3934.0 GR

NOTES: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-10-81 - RU Apache Services, perforated 1 hole @ each of the following intervals with 3 1/8" selective fire csg gun 4969, 61,57,56,55,4947,45,41,40,4936, 35,34,33,32,4928,27,26,22,19,13,4912,11, 23 holes, WIH with RTTS pkr, circ hole w/2% KCL water @ 4972, Spotted 100 gals MCA across perforation, set RTTS pkr @ 4877, acidized with 1500 gals 15% MCA - staged w/2 ball sealers per 65 gals acid, total of 40 ball sealers, flushed with 2% KCL water.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROBERT A. CHATMAN TITLE Production Secretary DATE 11-11-81

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

NOV 16 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

TITLE \_\_\_\_\_ DATE \_\_\_\_\_