

UNITED STATES OF NEW MEXICO 88248
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Brazos Petroleum Company

3. ADDRESS OF OPERATOR
P.O. Box 1782 - Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 660' FNL & 660' FEL
AT SURFACE:
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) XX

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-30-81 MI & RU Norton Drlg Co. rig #5, spudded @ 7:00 P.M. 9-29-81. Drld 12 1/4" Hole to 427', ran 10 jts 8 5/8" 24# K55 ST&C csg & set @ 427' KB, ran csg w/guide shoe, insert type-auto fill baffle & 3 centralizers, cemented w/ 300 sx Class "C" w/1/4# flocele per sx, 2% CaCl2, circulated an est. 90 sx cement to surface, plug down @ 4:15 A.M. 9-30-81.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN
(This space for Federal or State office use)

TITLE Production Secretary DATE 9-30-81

APPROVED BY ROGER A. CHAPMAN
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side