

UNITED STATES GEOLOGICAL SURVEY
DEPARTMENT OF THE INTERIOR
BOSTON, NEW MEXICO 88240

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other
-
2. NAME OF OPERATOR
Brazos Petroleum Company
-
3. ADDRESS OF OPERATOR
P.O. Box 1782 - Midland, Texas 79702
-
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL & 1980' FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same
-
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
240 LC 063623
-
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
-
7. UNIT AGREEMENT NAME
-
8. FARM OR LEASE NAME
Kringel Federal
-
9. WELL NO.
2
-
10. FIELD OR WILDCAT NAME
Sawyer (San Andres)
-
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 31, T-9-S. R-38-E
-
- | | |
|-----------------------------|-------------------------|
| 12. COUNTY OR PARISH
Lea | 13. STATE
New Mexico |
|-----------------------------|-------------------------|
-
14. API NO.
-
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3943.6 GR

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other) XX	

□ □ □ □ □ □ □ □

RECEIVED
OCT 1 1981

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-29-81 RTD 5020', reached TD @ 5:45 P.M. 9-28-81, circulated 2 1/2 hrs, POH LDDP, DC's & bit, ran 125 jts (5063.73') 4 1/2" 10.5# K55 ST&C csg with guide float shoe with auto fill & latch down assembly, 6 centralizers, set csg @ 5020', cementing @ report time with 800 sx 3% "C" Econolite w/8# salt per sx. & 1/4# flocele per sx. tail-in w/3-- sx 50:50 "C" POZ w/6# salt per sx & 1/4# flocele per sx.

9-30-81 Plug down @ 7:30 A.M. 9-29-81 - Circulated an est. 40 sx cement to surface, float held O.K., set slips, cut off csg, released rig @ 9:00 A.M. 9-29-81.
RD & MORT.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN TITLE Production Secretary DATE 9-30-81

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO