

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
HOBBS, NEW MEXICO 88240

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Brazos Petroleum Company

3. ADDRESS OF OPERATOR
P.O. Box 1782 - Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650' FEL & 1980' FSL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
LC 063623

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Kringel Federal

9. WELL NO.
4

10. FIELD OR WILDCAT NAME
Sawyer (San Andres)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 31, T-9-S, R-38-E

12. COUNTY OR PARISH
Lea

13. STATE
New Mexico

14. API NO.


15. ELEVATIONS (SHOW DF, KDB, AND WD)
3935.5 GL

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 10-10-81 RTD 428', Red Beds made 428' last 24 hrs, Spudded @ 1:00 A.M. 10-10-81.
Bit #1 12 1/4" retip made 428' in 4 hrs, POH, presently running 8 5/8" csg.
- 10-11-81 Drlg 7 7/8" hole @ 1346', Red Beds, made 918' last 24 hrs, Ran 10 jts (416.20')
8 5/8" 24# K55 ST&C csg set @ 428' KBM, cemented with 300 sx Class "C" with 2%
CaCl2 & 1/4# flocele per sx. Circulated 40 sx to surface, plug down @ 10:30 A.M.
10-10-81. Ran csg with Texas Pattern Shoe, 3 centralizers and insert type float
valve with automatic fill-up, float held O.K.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN TITLE Production Secretary DATE 10-12-81

(This space for Federal or State office use)

APPROVED BY OCT 15 1981 TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO