

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> <small>DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
		5. State Oil & Gas Lease No. L-6750
1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Brazos Petroleum Company		8. Farm or Lease Name Bass "A" State
3. Address of Operator P.O. Box 1782 - Midland, Texas 79702		9. Well No. 1
4. Location of Well UNIT LETTER <u>N</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM <u>West</u> LINE, SECTION <u>5</u> TOWNSHIP <u>10-S</u> RANGE <u>37-E</u> NMPM.		10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 3982.2 GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
		OTHER <u>XX</u>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-18-81 RTD 437', Red Beds, made 437' last 24 hrs, presently running 8 5/8" csg, spudded @ 10:00 P.M. 10-17-81.

10-19-81 Drlg 7 7/8" hole @ 1325', Red Beds, made 888' last 24 hrs, ran 10 (427') jts 8 5/8" 24# K55 ST&C csg set @ 437' ran csg with Texas Pattern Notched Shoe, insert baffle & 2 centralizers, cemented with 300 sx Class "C" with 2% CACL2 and 1/4# flocele per sx. Circulated 25 sx cement to surface, plug down @ 10:45 A.M. 10-18-81.

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Candice R. Sexton TITLE Production Secretary DATE 10-19-81

Orig. Signed By  
Jerry Sexton

APPROVED BY Dick L. Supp TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

OCT 23 1981