STATE OF NEW	DEPARTMENT	TION DIVISION	
DISTRIBUTION	P. O. BOX SANTA FE, NEW	X 2088	Form C-103 Revised 10-1-78
FILE U.S.G.S. LAND OFFICE			Sa. Indicate Type of Lease State Fee X
OPERATOR			5. State OII & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS 100 NOT USE THIS FOR PROPOSALS TO BAILL OF TO DEEPEN OF PLUE BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" IFORM C-1011 FCR SUCH PROPOSALS.)			7. Unit Agreement Name
OIL X CA	ат отнев-		
Alpha Twenty-One Production Company			8. Form or Lease Name Rae 9. Well No.
P.O. Box 1206 Jal, New Mexico 88252			1
OCCULION OF WELL UNIT LETTER P 990 FEET FROM THE South LINE AND 330 FEET FR			10. Field and Pool, or Wildcat
	LINE, SECTION 23 TOWNSHIP		
THE			···· ()))))))))))))))))))))))))))))))))
	15. Elevation (Show whether 4336 GL		12. County Lea
	Check Appropriate Box To Indicate N		
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
FORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
APORARILY ABANDON		COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
L OR ALTER CABING	CHANGE PLANS	CASING TEST AND CEMENT JOB	<u> </u>
OTHER			
Describe Proposed or C workj SEE RULE 1103	Completed Operations (Clearly state all pertinent deta	ills, and give pertinent dates, includi	ing estimated date of starting any proposed
11-15-82		vlyanian and Wolfcamp 5	
11-15-82 Came up hole to try the Pennsylvanian and Wolfcamp Zones. 11-16-82 Set Halliburton Retrievable Bridge Plug at 8550'. 11-17-82 Perforated on the first run8359,8360,8376,8378,8380,8410,8420,8428, 8434,8438,8446 and 8448 (12 shots total).			
	Perforated on the second run 8300 and 8302 (10 shots total		3282,8284,8286,8288,
11-18-82	Acidized lower set of perforations (8359-8448) with 4000 gals. of 15% NE-HCl acid. Set RTTS at 8350' for acid job. Swabbed. Eventually swabbed dry.		
11-23-82	Set Halliburton RBP at 8350'. Acidized upper set of perforations (8232- 8302) with 3000 gals. of Mod-202 acid. Swab back and test well.		
12-7-82	By verbal agreement with the Oil Commision: 1.) Set first CIBP by Welex at 9450' to seal off perforations at 9479-9521 and 9688-9696. Dumped 4 sks. of Class 'C' cement (35') on top of CIBP at 9450'. Estimated top of cement to be at		
hereby certify that the	Information, above is true and complete to the best o	f my knowledge and belief. 941	[5 ¹ .
. Much	int DC TITLE Dr	illing Superintendent	DATE <u>12-14-82</u>
Ell.	Ules TITLE OF	L & GAS INSPECTO	JAN 14 1503
DITIONS OF APPROV			11

42 ini 1021

RECEIVED DEC 1 5 1982 HOBBS GENCE

4

•

-