

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well  
2. NAME OF OPERATOR  
Delta Drilling Company  
3. ADDRESS OF OPERATOR  
3100 C North A Midland, Texas 79705  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 860' FSL & 660' FWL  
AT TOP PROD. INTERVAL: 860' FSL & 660' FWL  
AT TOTAL DEPTH: 860' FSL & 660' FWL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input checked="" type="checkbox"/>
(other) <input type="checkbox"/>	

5. LEASE

NM 15902-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Delta McGuffin Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat Wolfcamp

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

35 T9S 32E

12. COUNTY OR PARISH  
Lea

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4298

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. 7-3-84 - Set 5½" CIBP at 8400' and cap with 50' of cement.
2. 7-6-84 - Spot 25 sack plug at 3600'. Tag plug at 3354'.
3. 7-6-84 - Spot 40 sack plug at 2050', 50' inside of 5½" casing stub.
4. 7-7-84 - Tag plug at 1918'.
5. 7-7-84 - Spot 40 sack plug from 475' to 375'.
6. 7-7-84 - Spot 20 sack plug from 60' to surface.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ron Brown TITLE Sr. Engineer DATE 7/13/84

Orig. Sgd. Linda S. C. Randall (This space for Federal or State office use)

APPROVED BY Acting Area Manager TITLE \_\_\_\_\_ DATE 1-26-87  
CONDITIONS OF APPROVAL, IF ANY: