## UNITED パップラス DEPARTMENT OF THE INTERIO GEOLOGICAL SURVEY

UNITED (3) TS  DEPARTMENT OF THE INTERIOR  GEOLOGICAL SURVEY	5. LEASE  NM 15902-B  6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME  8. FARM OR LEASE NAME Delta McGuffin Federal
1. oil gas well other	9. WELL NO.
2. NAME OF OPERATOR Delta Drilling Company	10. FIELD OR WILDCAT NAME Wildcat Wolfcamp
3. ADDRESS OF OPERATOR 3100 C North A Midland, Texas 79705 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 35 T9S 32E
below.) AT SURFACE: 860' FSL & 660' FWL AT TOP PROD. INTERVAL: 860' FSL & 660' FWL	12. COUNTY OR PARISH 13. STATE New Mexico  14. API NO.
AT TOP PROD. INTERVAL.  AT TOTAL DEPTH: 860' FSL & 660' FWL  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO:  TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON*  SUBSEQUENT REPORT OF:  SUBSEQUENT REPORT OF:	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly st including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertired.)	
1. 7-3-84 - Set 5½" CIBP at 8400' and can wit 2. 7-6-84 - Spot 25 sack plug at 3600'. Tag p 3. 7-6-84 - Spot 40 sack plug at 2050', 50' i	h 50' of cement.
3. 7-6-84 - Spot 40 sack plug at 2000; 30	A SECTION AND A

17. DESCRIBE PROPOSED OR COMPLETED OPERA including estimated date of starting any propose measured and true vertical depths for all marker 1. 7-3-84 - Set 5½" CIBP at 8400'
2. 7-6-84 - Spot 25 sack plug at 3 3. 7-6-84 - Spot 40 sack plug at 2 4. 7-7-84 - Tag plug at 1918' 5. 7-7-84 - Spot 40 sack plug from 475' to 375'. 6. 7-7-84 - Spot 20 sack plug from 60' to surface. Set @ \_.... ---Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct TITLESr. Engineer DATE 7/13/84 (This space for Federal or State office use) TITLE APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

RECRIVED

APR -3 1985

CAN Heller Mark