

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
K-1765

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - II" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Cities Service Company	8. Form or Lease Name State DV
3. Address of Operator P.O. Box 1919 - Midland, Texas 79702	9. Well No. 1
4. Location of Well UNIT LETTER <u>L</u> <u>2310</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>23</u> TOWNSHIP <u>12S</u> RANGE <u>32E</u> N.M.P.M.	10. Field and Pool, or Wildcat Caprock Penn, East
15. Elevation (Show whether DF, RT, GR, etc.) 4338' GR	12. County Lea

15. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 10,450' Lime, Shale and Sand. Prep to complete well. Drilled a 7-7/8" hole to a T.D. of 10,450' in Lime, Shale and Sand. Ran and set 192 Jts.(8121.38') of 5-1/2"OD 17# and 53 Jts. (2312.84') of 5-1/2"OD 15.5# casing @ 10,450' and cemented w/230 sacks of Lite Poz-Class C 65-35 w/4% gel, 7# salt & 0.2 of 1% D46/sack + 750 sacks of Class C w/0.2 of 1% D46/sack cement. PD @ 0855 MDT on 10-22-82. PU BOP's, set slips and CO csg. NU WH and tested to 1500#. Ran Temp. Survey. Top of cement @ 6650'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Elmer Startz TITLE Reg. Opr. Mgr. - Prod. DATE 12-1-82

ORIGINAL SIGNED BY
APPROVED BY JERRY SEXTON TITLE DISTRICT SUPERVISOR DATE DEC 3 1982

RECEIVED

DEC 2 1982

O.C.D.
HOBBS OFFICE