

CAL CONSERVATION DIVISION
P. O. BOX 2038
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-7

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ For ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFEAT OR PLUG SALS TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (IFC&M C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. Name of Operator
Jubilee Energy Corporation
3. Address of Operator
3100 N. "A", Bldg. E, Suite 103, Midland, Texas 79705
4. Location of Well
UNIT LETTER F 1980 FEET FROM THE North LINE AND 1980 FEET FROM
THE West LINE, SECTION 21 TOWNSHIP 9-S RANGE 34-E N.M.P.M.

7. Unit Agreement Name
8. Farm or Lease Name
Pruitt "21"
9. Well No.
1
10. Field and Pool, or Wildcat
Vada-Penn
12. County
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPERATIONS ☒
PULL OR ALTER CASING ☐ OTHER ☐ CASING TEST AND CEMENT JOBS ☒
SUBSEQUENT REPORT OF:
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-07-83 Commenced drilling at 5:00 a.m.
2-08-83 Drilled to 398' and ran 13 3/8" casing to 398' and cemented w/275 sx. Class "C" cement w/2% CaCl. Cement circulated. WOC 18 hrs. Install BOP. Test 500# for 30 minutes. Test okay.
2-14-83 Drilled to 4014' and running 8 5/8" casing - casing parted @ 2024'. Cut off casing at 2020' and ran casing patch. Did not hold. Prep to sidetrack. Spotted 200 sx. plug @ 2000'. WOC 18 hrs. Spotted additional plug at 1823'. WOC 18 hrs. Drilled to 4010' and ran 8 5/8" casing to 4010' and cemented w/850 sx. in two stages. (200 sx. Class "C" w/2% CaCl - DV tool @ 2116'; 500 sx. Lite Poz + 150 sx. Class "C" cement) Circulated cement. WOC 18 hrs.
3-21-83 Reached TD of 9852'. Ran GR-Acoustic log. Ran 5 1/2" casing to TD and cemented w/200 sx. Class "C" w/2% CaCl.
4-10-83 Perforated 5 1/2" casing from 9804' to 9810' w/12 shots.
4-11-83 Acidized perforations w/500 gallons 15% Hcl. Max. Pressure - 500 psi. 5 1/2" casing collapsed @ 7740'.
5-05-83 Cut 5 1/2" casing @ 7702'. Pulled and recovered 7702'.
5-10-83 Spot 100 sx. Class "C" cement plug @ 7702'. Drilled to 7400'. Side track 5 1/2" casing to 9858' TD.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED _____ TITLE President DATE 7-27-83

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT SUPERVISOR

TITLE _____ DATE _____

AUG 1 1983