STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

CHOI ATTIVITY CONCOLO	_, _,	-
HO, OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
116		
U.S.G.S.	_	
LAND OFFICE		
00==++0=	1	l

OIL CONSERVATION DIVISION

		_				
Form	C-	1	0.3			
Revis	e d		10	- '	ì -	7

DISTRIBUTION	P. O. BOX 2088			Revised	10-1-70
SANTA FE	SANT	SANTA FE, NEW MEXICO 87501			
TILE	-			Sa. Indicate Type of Lease	(V)
U.S.G.S.	4				• [X]
OPERATOR	-	٠		5, State OII & Gas Lease No.	
	. است				
SLINDS	RY NOTICES AND R	EPORTS ON	WELLS ACK TO A DIFFERENT RESERVOIR.		
(DO NOT USE THIS FORM FOR PA	CPOSA S TO DRILL OR TO CE	C-101) FOR SUC	ACK TO A DIFFERENT RESERVOIR.		7]]]
				7. Unit Agreement Name	
OIL GAS WELL WELL	OTHER- Dry				
Name of Operator				3. Farm or Lease Lame	
Sulpetro Resou	urces Inc			Wood Oil Co.	
Address of Operator	irees, riie.			9. Well No.	
	Plaza 6730 LRI	Frwy. Da	11as, Texas 75240		
	11aza, 0750 BB0	11wy., De	11146, 16446 75210	10. Field and Pool, or Wildow	
. Location of Well	10001	NI or on to be	6601	Vada Penn	
UNIT LETTER	1980 FEET FROM TH	North	LINE AND DOUF	EET FROM	777
			2/7		[[]]
THEEastLINE, SECT	10H 79 TOW!	чэнIР9S	RANGE34E	_ NMPN: ([[]]]]]]]	////
				<u> </u>	444
	.15, Elevation			12. County	////
		4271.4	GR	Lea	777
6. Check	Appropriate Box T	o Indicate N	ature of Notice, Repor	t or Other Data	
	INTENTION TO:		SUBSE	EQUENT REPORT OF:	
NOTICE	1112111011101				
	PLUC AN	I ABANDON	REMEDIAL WORK	ALTERING CASING	
PERFORM REMEDIAL WORK			COMMENCE DRILLING OPHS.	PLUG AND ABANDONA	ENT
HOOMABA YJERAROHMET			CASING TEST AND CEMENT JOB		_
PULL OR ALTER CASHIG	CHANGE	PLANS			
		<u></u>	OTHER		
OTHER					
	Clearly state	all pertinent det	ails and give pertinent dates.	including estimated date of starting any	propose
7. Describe Proposed of Completed C work) SEE RULE 1103.	perduons (Creamy state of	arr perrinent der	and gree process		
•			100/00 C 00 P 16		
	egin plugging op	eration 3,	/23/83 at 6:30 P.M.	Completed plugging	
3/29/83 .					
Cement plugs	spotted with 40	sx. each	olug at:		
9830'-9730',	7546'-7644', 755	50'-7450',	6650'-6750'		
				and 1500'-1400' with 40 s	X.
Finished spot	ting cement plug	gs @ 4100 ·	-5940 WILL OU SA:	steed pits. Woight of	7 •
Layed down 4½	" DP and N/D BOR	rs, cut o	or toll head and Je	etted pits. Weight of	
Mud was 9.5.	Casing left in	hole was	8-5/8" csg. at 3990	and 11-3/4" at 427'	
	,				
•					
8. I hereby certify that the information	on above is true and comp	lete to the best	of my knowledge and belief.		
√ // \					
// Mana	H. Timm	Pr	oduction Manager	DATE 4/5/83	
ICHED - AMERICAN			=		
ORIGINAL SIGNED I	BY JERRY SEXTON			BAYE APR 1 1 19	183
ARRONTO BY DICTURE	UBEDVICOR	TITLE		DATE [[1] 1] L L L L	

APPROVED BY _____DISTRICT | SUPERVISOR

CONDITIONS OF APPROVAL, IF ANY: