

This form is to be filled with the appropriate District Office of the Commissioner at later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filled in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2344'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen 2820'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3642'	T. Simpson	T. Gallup	T. Ignacio Qtzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand	T. Entrada	T.
T. Abo	T. Bone Springs	T. Wingate	T.
T. Wolfcamp	T. Penrose	T. Chinle	T.
T. Penn.	T. Premier	T. Permian	T.
T. Cisco(BoughC)	T. Lovington	T. Penn "A"	T.
T.	T.	T.	T.

OIL OR GAS SAND OR ZONES

No.1, from.....to.....	No.4, from.....to.....
No.2, from.....to.....	No.5, from.....to.....
No.3, from.....to.....	No.6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No.1, from.....to.....	feet.....
No.2, from.....to.....	feet.....
No.3, from.....to.....	feet.....
No.4, from.....to.....	feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
2344'	2820'	476'	Shale, Anhydrite & Sandstone				
2820'	3642'	822'	Sandstone, Anhydrite & Dolomite				
3642'	4173'	531'	Sandstone, Dolomite & Anhydrite				
4173'	4328'	155'	Sandstone, Dolomite, Anhydrite & Shale				
4328'	4497'	169'	Dolomite, Anhydrite & Limestone				

APR 24 1984
HOBBS
OFFICE