

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISS

Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR NOTICES TO ABANDON OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR REPORT ON PRODUCE, FOR SUCH PURPOSES.)		5a. Indicate Type of Lease State ☒ Fee ☐
1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER		5. State Oil & Gas Lease No. K-6857
2. Name of Operator V-F Petroleum Inc.		7. Unit Appraisal Date
3. Address of Operator Suite 580, One Marienfeld Place, Midland, Texas 79701		8. Name of Lease Name State 32
4. Location of Well UNIT LETTER P 900 FEET FROM THE South LINE AND 330 FEET FROM THE East LINE, SECTION 32 TOWNSHIP 9S RANGE 37E NMPH.		9. Well No. 2
15. Elevation (Show whether DF, RT, GR, etc.) 3966		10. Field and Pool, or Well San West Sawyer, Andres
12. County Lea		

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CHANGE PLANS ☐	REMEDIAL WORK ☐ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOG ☐ OTHER ☐	ALTERING CASING ☐ PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-30-83 - Spudded well at 8 am 7/30/83 with rat hole machine. Drilled 30' of surface. SD. WORT.

7-16-83 MIRT. Drill 12 1/4" hole to 455'. Ran 8 5/8" csg to 455' & cmt w/370 sx Cl "C". Circ 50 sx to surface. WOC 12 hrs. Install BOPE & test to 1000 psi.

8-17 to 22-83 Drill 7 7/8" hole to 4771'. Encountered 400 BPH water flow at 3250'. Could not drill on because of sloughing red bed.

8-22 to 30-83 Mix and pump 2000 bbls heavy mud in attempt to control water flow without success. POH w/Drill pipe. Attempt to go to TD to P & A well. Could not get drill pipe below red beds at 1500'.

8-31-83 Cmt. well with 1000 sx Cl "C". Cmt drill pipe in hole at 1479'. No flow to surface after WOC 12 hrs. Cut off drill pipe & 8 5/8" csg. Weld cap on csg & install dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>C. Englem</u>	TITLE <u>Opns. Mgr.</u>	DATE <u>12/7/83</u>
APPROVED BY <u>David Catanzar</u>	TITLE <u>OIL & GAS INSPECTOR</u>	DATE <u>APR 9 1984</u>
CONDITIONS OF APPROVAL, IF ANY:		