

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-28463
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
APACHE CORPORATION

3. Address of Operator
3300 N. "A", STE 8220 MIDLAND, TX 79705

4. Well Location
Unit Letter H : 990 Feet From The EAST Line and 1650 Feet From The NORTH Line
Section 36 Township 11S Range 37E NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3892.8 GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Set CIBP on Wireline @ 12,000'. Dump bail 5 sx. on plug.
2. TIH w/tbg. to 11,050 Circ. hole w/mud laden fluid.
3. Spot 25 sx. cmt. from 8825' - 9050'.
4. Spot 25 sx. cmt. from 5775' - 6000'.
5. Spot 40 sx. cmt. from 4300' - 4620'.
6. Cut 5½" csg. @ 4050'. POOH.
7. Spot 50 sx. cmt. from 3920' - 4120'. WOC & TAG.
8. Circ. hole w/mud laden fluid.
9. Spot 40 sx. cmt from 2200' - 2340'.
10. Spot 40 sx. cmt from 150' - 290'.
11. Spot 15 sx. cmt. from 50' - surface.
12. Install 4½" dry hole marker.

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David Belew TITLE Rig Superintendent DATE 10/27/97

TYPE OR PRINT NAME David Belew TELEPHONE NO.

(This space for State Use)
APPROVED BY GARY W. WINK TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:
OCCUPED REPRESENTATIVE II/STAFF MANAGER