

OIL CONSERVATION DIVISION
 P. O. BOX 2088
 SANTA FE, NEW MEXICO 87501

Form C-103
 Revised 10-1-70

BY WHOM RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.C.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
 State ☒ Fee ☐
 5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER	7. Unit Agreement Name
2. Name of Operator Harper Oil Company	8. Farm or Lease Name Heyco "36" State
3. Address of Operator 904 Hightower Bldg., Oklahoma City, OK 73102	9. Well No. #1
4. Location of Well: UNIT LETTER <u>H</u> <u>990</u> FEET FROM THE <u>East</u> LINE AND <u>1650</u> FEET FROM THE <u>North</u> LINE, SECTION <u>36</u> TOWNSHIP <u>11S</u> RANGE <u>37E</u> N.M.P.M.	10. Fluid and Pool, or Wildcat Gladiola <i>Devonian</i>
15. Elevation (Show whether DF, RT, GR, etc.) G.L. 3892.8'	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-4-84 Reached TD @ 5:00 PM 1/31/84. Circ. @ 12,505' TD. RU and ran 305 jts. 5½" casing. Prep to cement. Ran 35 jts. 20# N-80 (1438.38'); 60 jts. 17# N-80 LT&C (2400.88'); 24 jts. 17# K-55 LT&C (1044.67'); 94 jts. 17# J-55 LT&C (3946.64'); 10 jts. N-80 LT&C (400.61'); DV tool (3.10'); 52 jts. 17# N-80 LT&C (2083.55'); 27 jts. 20# N-80 LT&C (1152.16'); float collar (1.55'); 1 jt. 20# N-80 LT&C (40.10'); guide shoe (40.10'); shoe set @ 12,504.00'; guide shoe @ 12,502.20'.

2-5-84 RU Howco. Mixed & pumped 735 sx Class H containing .6% Halad 22-A, .4% CFR-2, 5#/sk. KCL. Bumped plug. Open DV tool. Circ. 4 hrs., mix & pump 675 sks Class H plus additives. Bump plug w/2000 psig. Closed DV tool. Cleaned pits. Released rig @ 8:00 PM 2-4-84.

2-6-84 W.O. Completion.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Jerry Sexton* TITLE Production Manager DATE 2-9-84

ORIGINAL SIGNED BY JERRY SEXTON
 DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____

FEB 14 1984