

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-6428
7. Unit Agreement Name
8. Farm or Lease Name Wiser State
9. Well No. 3
10. Field and Pool, or Wildcat E. Crossroads-SA
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator
M. C. Gandy & Dale Gandy

3. Address of Operator
c/o Oil Reports & Gas Services, Inc., Box 763, Hobbs, NM 88241

4. Location of Well
UNIT LETTER D 660 FEET FROM THE North LINE AND 655 FEET FROM
THE West LINE, SECTION 18 TOWNSHIP 10S RANGE 37E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3977.4 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 5:00 PM 2/1/84. Cemented 8 5/8" 24# J-55 casing st 407' with 225 sacks class "C", 2% calcium chloride. Plug down 10:20 PM. Cement circulated to surface. WOC 12 hours. Pressure test casing with 750# for 30 minutes, test O.K.

Cemented 4 1/2" 9.5# J-55 casing at 4936 with 875 sacks lite, 219 sacks celloseal & 100 sacks class "C". Plug down 2:45 PM 2/10/84. Trace of cement to surface. Loaded 4 1/2"-8 5/8" annulus with 40 gallons KCl water. Pressured to 500#, held O. K. Estimated top cement behind 4 1/2" casing 10' below surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton TITLE Agent DATE 3/6/84

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON TITLE DISTRICT 1 SUPERVISOR
CONDITIONS OF APPROVAL, IF ANY:

MAR 7 1984

RECEIVED

MAR 6 1984

O.C.D.
HOBBS OFFICE