

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.

30-025-24647

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

KELLAHIN 14 STATE

8. Well No.

1

9. Pool name or Wildcat

FLYING M (PENNY) Bough

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL

WELL ☒

GAS

WELL ☐

OTHER

2. Name of Operator

SPENCE ENERGY COMPANY

3. Address of Operator

4849 GREENVILLE AVE., #381, DALIAS, TX 75206

4. Well Location

Unit Letter I : 810 Feet From The EAST

Section 14

Township 9S

Range 32E

Line and 1980

Feet From The SOUTH

Line

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

NMPM

LEA

County

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

REPAIR OR ALTER CASING ☐

OTHER: ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- (1) MOVE IN & RIG UP. RUN TUBING. TAG PLUG @ 8858'.
- (2) LOAD HOLE WITH MUD.
- (3) SPOT 25 SK. CEMENT PLUG @ 8100'. W.O.C. TAG PLUG @ 7936'.
- (4) CUT 5 1/2" CSG. @ 4579'. PULL & LAY DOWN.
- (5) SPOT 100 SK. CEMENT PLUG @ 5 1/2" STUB. WOC. TAG PLUG @ 4269'.
- (6) SPOT 50 SK. CEMENT PLUG @ 4010'. WOC. TAG PLUG @ 3645'.
- (7) CUT 8 5/8 CASING @ 717'. LAY DOWN.
- (8) SPOT 80 SK. CEMENT PLUG @ 1600'.
- (9) SPOT 60 SK. CEMENT PLUG @ 767'. WOC. TAG PLUG @ 652'.
- (10) SPOT 80 SK. CEMENT PLUG @ 450'. WOC. TAG PLUG @ 333'.
- (11) SPOT 10 SK. SURFACE PLUG & INSTALL P & A MARKER.

certify that the information above is true and complete to the best of my knowledge and belief.

BY Raymond Maldonado/KH TITLE P & A SUPERVISOR

PRINT NAME RAYMOND MALDONADO

DATE 1-18-90

for State Use)

BY Jack Griffin

IS OF APPROVAL, IF ANY:

OIL & GAS INSPECTOR

TITLE

DATE

TELEPHONE NO. 505-393-5516

MAY 31 1990