

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)		
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator RONADERO COMPANY, INC.		8. Farm or Lease Name RONALTO
3. Address of Operator P. O. BOX 430, ROSWELL, NEW MEXICO 88201		9. Well No. 2
4. Location of Well UNIT LETTER <u>0</u> <u>2310</u> FEET FROM THE <u>EAST</u> LINE AND <u>330</u> FEET FROM THE <u>SOUTH</u> LINE, SECTION <u>14</u> TOWNSHIP <u>12S</u> RANGE <u>32E</u> NMPM.		10. Field and Pool, or Wildcat EAST CAPROCK PENN
15. Elevation (Show whether DF, RT, GR, etc.) 4330.8 GL		12. County LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9/28/85 - Ran 254 jts (10,569') 5½", 17#, N-80 & J-55 LT&C casing and set @ 10,550' - cemented w/600 sxs Class "H" & 50-50 poz & 4/10 of 1% F.L. 19 and 200 sxs Class "H"-Neat & 4/10 of 1% F.L. 19 - plug down @ 2:00 a.m. on 9/29/85. Pressured up to 1500# on casing. Held OK for 15 min.

9/29/85 - Temperature survey indicates top of cement @ 7,500'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Rubert W. Flanagan</u>	TITLE <u>Vice President</u>	DATE <u>10-3-85</u>
APPROVED BY <u>Eddie W. Seay</u> <u>Oil &amp; Gas Inspector</u>	TITLE _____	DATE <u>OCT 7 - 1985</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED  
OCT -7 1985  
C-62  
HOBBS OFFICE