

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for each proposal.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	6. LEASE DESIGNATION AND SERIAL NO. NM-60414
2. NAME OF OPERATOR Manzano Oil Corporation	7. UNIT AGREEMENT NAME
3. ADDRESS OF OPERATOR P.O. Box 571, Roswell, NM 88202 505/623-1996	8. NAME OF LEASE NAME Clemmons Sunburst Federal
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FSL & 1980' FEL	9. WELL NO. 2
14. PERMIT NO.	10. STEEL AND POOL, OR WILDCAT Flying "M" South
15. ELEVATIONS (Show whether SF, ST, SA, etc.) 4368.9 GL	11. SEC., T., R., N., OR D.R. AND SUFFIX OF AREA Sec. 13-T9S-R32E
	12. COUNTY OR PARISH Lea
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	PLUG OR ALTER CASING
FRACTURE TREAT	MULTIPLE COMPLETE
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANE
(Other)	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other) Running Intermediate Casing	X
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all matters and zones pertinent to this work.)

9/17/85 Ran and cemented 13-3/8" casing. See previous report.

9/22/85 Drilled 12-1/4" hole to 3600'. Received verbal approval from Bob Pitschke at BLM/Carlsbad, NM to set 8-5/8" casing @ 3600' instead of 3760'.
Ran 85 joints, 3609', 8-5/8" 24 & 32# csg; Set and cemented @ 3600' with 1300 sacks Halliburton Lite w/15# salt & 3# gilsonite per sack PLUS 300 sacks Class C w/2% CaCl. Circulated 165 sks to surface. Plug down @ 9:30 a.m. 9/22/85. Pressure up to 1200# for 30 minutes, held OK.
Casing ran: 32 jts - 1374.20' 32# 8-5/8"
50 jts - 2107.78' 24# "
3 jts - 126.02' 32# "
85 jts - 3608.00'

8-6-86

To BLM - Do you have a completion report on this well? Please advise

Thanks Evelyn Hobbs OCP

18. I hereby certify that the foregoing is true and correct.	TITLE Jackie Midkiff/Prod. Clerk	DATE 9/23/85
SIGNED <u>Jackie Midkiff</u>		
(This space for Federal or State office use)		
APPROVED BY <u>RECEIVED FOR RECORD</u>	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		

001 1 1985

*See Instructions on Reverse Side