

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

(Other instructions on reverse side)

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. NM-56545
2. NAME OF OPERATOR Manzano Oil Corporation 505/623-1996		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P.O. Box 571, Roswell, NM 88202		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330' FSL & 330' FWL		8. FARM OR LEASE NAME Sunburst Spence Federal
14. PERMIT NO. 30-025-29578		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, OR, etc.) 4337'		10. FIELD AND POOL, OR WILDCAT Undesignated
		11. SEC., T., R., N., OR S.W. AND SURVEY OR AREA Sec 13-T9S-R32E
		12. COUNTY OR PARISH Lea
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☒ Casing and Cement job	

(Note: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1/19/86 Spudded 17 1/2 hole @ 7:45 p.m. 1/18/86.
Drilled to 350'. Ran 9 joints (367') of 13-3/8" 61# casing, set and cemented @ 350' with 350 sacks Class C with 2% calcium chloride, circulated 100 sacks to surface, plug down @ 10:30 a.m. 1/19/86. Pressured to 600#, held ok.
Witnessed by Jack Johnston of BLM.

1/25/86 Drilled to 3590'. Ran 86 joints (3598') of 8-5/8" J55 ST&C 24 & 32# casing. Set and cemented @ 3590' with 1300 sacks Halliburton Lite with 15# salt & 1/4# floreal & 3# gilsonite per sack, followed by 300 sacks Class C with 2% calcium chloride, circulated 100 sacks to surface. Plug down @ 12:40 a.m. 1/25/86. Pressured to 1000#, held OK.

ACCEPTED FOR RECORD

Swed
FEB 11 1986

CAPISBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Jackie Midkiff/Prod. Clerk

DATE 2/10/86

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED
FEB 11 1986
C. C. C.
HOBBS OFFICE