

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-101
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry		7. Unit Agreement Name	
2. Name of Operator Tenneco Oil Company		8. Farm or Lease Name State SG25	
3. Address of Operator 7990 IH 10 West, San Antonio, Texas 78230		9. Well No. 1	
4. Location of Well UNIT LETTER I, 1980 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 25 TOWNSHIP 10S RANGE 32E NMPM.		10. Field and Pool, or Wildcat Cuerno Largo Penn	
15. Elevation (Show whether DF, RT, GR, etc.) 4276.4 GR		12. County Lea	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7 7/8" hole to 10,500'.

Logged hole with MICRO-DLL-GR- Log.

P&A'd well with balance cement plugs at 9510'-9410', 8600'-8500', 6570'-6470', 5150'-5050', plug @ shoe 3825'-3725', 1860'-1760' 380'-280', set 10 sacks @ surface, welded plate over casing and installed dryhole marker. Rig released @ 6:00 p.m. on 2/19/87.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Don Lindsey

TITLE Drilling Engineer

DATE 3/4/87

APPROVED BY Jack Griffin

TITLE OIL & GAS INSPECTOR

DATE MAR 7 - 1988

CONDITIONS OF APPROVAL, IF ANY:

DA C. L. M. S.

RECEIVED
MAR 6 1987
OCD
HOBBS OFFICE