

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			Northwestern New Mexico		
Rustler	2098				
T. Anhy		T. Grayson XX Mkr 9201	T. Ojo Alamo		T. Penn. "B"
T. Salt		T. Grayson 3 Bros. 9584	T. Kirtland-Fruitland		T. Penn. "C"
B. Salt		T. Grayson BO A 9842	T. Pictured Cliffs		T. Penn. "D"
T. Yates	2756	T. Grayson BO B 9891	T. Cliff House		T. Leadville
T. 7 Rivers		T. Grayson BO C 9944	T. Menefee		T. Madison
T. Queen	3620	T. Silurian	T. Point Lookout		T. Elbert
T. Grayburg		T. Montoya	T. Mancos		T. McCracken
T. San Andres	4060	T. Simpson	T. Gallup		T. Ignacio Qtzte
T. Glorieta	5476	T. McKee	Base Greenhorn		T. Granite
T. Paddock		T. Ellenburger	T. Dakota		T.
T. Elinebry		T. Gr. Wash	T. Morrison		T.
T. Tubb	6939	T. Granite	T. Todilto		T.
T. Drinkard		T. Delaware Sand	T. Entrada		T.
T. Abo	7741	T. Bone Springs	T. Wingate		T.
T. Wolfcamp	9094	T. Ranger Lake 10190	T. Chinle		T.
T. Penn.		T. Upper Cisco 10364	T. Permian		T.
T. Cisco (Bough C)		T. Lwr Cisco 10510	T. Penn. "A"		T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet	
No. 2, from.....to.....feet	
No. 3, from.....to.....feet	
No. 4, from.....to.....feet	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	410	410	Surface, Redbeds				
410	2164	1754	Redbeds				
2164	3480	1316	Anhy, Salt				
3480	4250	770	Anhy, Dolo				
4250	4820	570	Dolo, Cht, Shale				
4820	5340	520	Dolo, Sh, Lm				
5340	5480	140	Dolo, Sh, Lm, Cht				
5480	7100	1620	Dolo, Sh, Cht, Sd				
7100	7580	480	Dolo, Sh, Sd, Lm, Cht				
7580	7814	234	Dolo, Sh, Cht				
7814	8170	356	Shale, Cht				
8170	9080	910	Dolo, Sh, Cht				
9080	9590	510	Dolo, Sh, Lm, Cht				
9590	10575	985	Lm, Sh, Cht				