NO. OF COPIES RECEIVED		Form C-103 Supersedes Old
DISTRIBUTION		C-102 and C-103
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISS	SION Effective 1-1-65
FILE	- 	
U.S.G.S.	_	5a. Indicate Type of Lease
LAND OFFICE		State X Fee
OPERATOR	<u></u>	5. State Oil & Gas Lease No.
		V-2174
S (DO NOT USE THIS FORM USE "A	UNDRY NOTICES AND REPORTS ON WELLS FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RES PPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)	SERVOIR.
1. OIL GAS [7. Unit Agreement Name
2. Name of Operator	OTHER-	8. Farm or Lease Name
•	aumana Campany	State 24-26
Union Pacific Res 3. Address of Operator	ources company	9. Well No.
	in - 2000	
1000 Louisiana, S	uite 3000	
	0010	10. Field and Pool, or Wildcat
UNIT LETTER N	2310 FEET FROM THE WEST LINE AND 330	Wildcat (Devonian)
THE SOUTH LINE	, SECTION 26 TOWNSHIP 10S RANGE 33E	NMPM.
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
		Lea
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data		
		SUBSEQUENT REPORT OF:
	or in Entrol to:	SUBSCUDENT REPORT OF.
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	(T)
=	-	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING O	;
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMI	ENT JQL THE
	OTHER	
OTHER		
17. Describe Proposed or Compl	eted Operations (Clearly state all pertinent details, and give pertinent	dates, including estimated date of starting any proposed
work) SEE RULE 1 103.		
MIRU Norton Drilling Co. Spudded $11/16/87$. Drilled $17\frac{1}{2}$ " hole to 468. Ran 11 jts $13-3/8$ " OD		
54# J-55 ST&C casing and set @ 468. Cement casing w/475 sx Class C w/2% CaCl. Plug down @		
2:15 p.m. 11/17/87. Used 7 centralizers. Circluate 119 sx. Nipple up and test BOP's. WOC 21 hrs		
•		
Drilled 11" hole from 468'-4153'. Ran 100 jts 8-5/8" OD 32# (2077') and 24# (2076) J-55 csg to		
4153. Cement casing w/1400 sx Lite cement, 200 sx Class C w/2% CaCl. Plug down @ 10:30 p.m.		
11/23/87. Cement did not circulate. Used 4 centralizers. Ran Temperature survey. TOC @		
1000'. Nipple up and test BOP's. WOC 24 hrs.		
1000 . Nippic up a	nd test bor s. woo 24 mrs.	
Drilled 7-7/8" hole	from 4153'-12,800'.	
12/22/07. Ban P	CT #1 @ 11 6/5!	
	OST #1 @ 11,645'.	
	ST #2 @ 12,656'.	
1/14/88: Ran D	ST #3 @ 12,698'.	
	1 10 00 5 200 1 1=" 10 10 10 10 10 10 10 10 10 10 10 10 10	
Ran logs on 1-17 thru 1-19-88. Ran 302 jts 17# N-80 (9430') & P-110 (3370') casing and set @		
12,800'. Cement ca	sing $w/1000$ gals. mud flush, $800 \text{sx} 50-50$ P	Pozmix. Plug down @ 8:10 a.m. 1/20/88
Released rig 1/20/88 @ 6 p.m. WOC 168 hrs. 18. I hereby gently that the information above he true and complete to the best of my knowledge and belief.		
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
1 DA A		
SIGNED // Welchy	THE Regulatory Anal	yst February 25, 1988
,	,	

DATE FEB 29 1988

APPROVED BY ___

ORIGINAL SIGNED BY JERRY SEXTON

DISTRICT I SUPERVISOR