

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

3a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
3. State Oil & Gas Lease No.	
30-025-30174 1 H 103	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input checked="" type="checkbox"/> GAS <input type="checkbox"/> WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Form or Lease Name
APACHE CORPORATION		ECHOLS "18" STATE
3. Address of Operator		9. Well No.
7666 E. 61ST STREET, SUITE 500, TULSA, OK 74133		1
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER D 660 FEET FROM THE NORTH LINE AND 990 FEET FROM THE WEST LINE, SECTION 18 TOWNSHIP 11S RANGE 38E NMPM.		WILDCAT
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3916' GR		LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

THE SUBJECT WELL WAS SPUDDED AT 9:30 PM, JANUARY 1, 1988. RAN AND SET 13-3/8" 54.5# J55 STC CASING AT 450'. CEMENTED TO SURFACE WITH 475 SXS PREMIUM CLASS 'C' CEMENT WITH 2% CaCl₂. CIRCULATE 75 SXS TO SURFACE. PLUG DOWN AT 5:30 PM 01/02/88. WOC 24-1/2 HRS (6:00 PM 01/03/88). TEST CASING TO 1000 PSI FOR 30 MINUTES. NO BLEED-OFF. TEST OK. RESUMED DRILLING.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Gary L. Poulain</u>	TITLE <u>DRILLING ENGINEER</u>	DATE <u>01/08/88</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>DISTRICT 1 SUPERVISOR</u>	DATE <u>JAN 14 1988</u>
CONDITIONS OF APPROVAL, IF ANY:		