

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.
NA

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPERATE OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER - Dry Hole	7. Unit Agreement Name NA
2. Name of Operator MAXUS EXPLORATION COMPANY	8. Farm or Lease Name BEAR CLAW STATE
3. Address of Operator P.O. Box 10397 Midland, TX 79702	9. Well No. 1
4. Location of Well UNIT LETTER <u>FK</u> 660 FEET FROM THE North LINE AND 2160 FEET FROM THE West LINE, SECTION 6 TOWNSHIP 11-S RANGE 37-E NMPM.	10. Field and Pool, or Wildcat Undesignated Devonian
15. Elevation (Show whether DF, RT, GR, etc.) 3994' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

07-29-88 to 09-01-88 Drill to 12,408' with a prehydrated fresh water gel system. MW 9.8 ppg to 10 ppg. Log well by Schlumberger. Ran DLL/MFL/Caliper/LDT and Sonic/GR/Caliper.

09-01-88 to Plug well by Dowell as follows (per Mr. Paul Katuz of the New Mexico Oil Conservation Division)

Plug #1	12,349'-12,249'	50 sx Cl "H" w/0.2% D-13
Plug #2	10,099'- 9,999'	50 sx Cl "H" w/0.2% D-13
Plug #3	7,669'- 7,569'	60 sx Cl "H" Neat
Plug #4	5,639'- 5,539'	60 sx Cl "H" Neat
Plug #5	4,260'- 4,160'	45 sx Cl "H" Neat
Plug #6	2,300'- 2,200'	31 sx Cl "H" Neat
Plug #7	20'- Surface	10 sx Cl "H" Neat

All cement @ 16.4 ppg & 1.18 ft³/sk

Set dry hole markers. Released TMBR/Sharp Rig #22 09-02-88

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Graig Mickieberry</u>	TITLE <u>Sr. Drilling Engineer</u>	DATE <u>09-30-88</u>
APPROVED BY <u>Jack Krull</u>	TITLE <u>OIL & GAS INSPECTOR</u>	DATE <u>AUG 2 1988</u>
CONDITIONS OF APPROVAL, IF ANY:		