

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-30676
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-1239
7. Lease Name or Unit Agreement Name Lagarto State Unit
8. Well No. 1
9. Pool name or Wildcat Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter N : 660 Feet From The South Line and 1838.8 Feet From The West Line Section 18 Township 11S Range 35E NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4144' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Intermediate Casing <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-6-89. Ran 98 joints 8-5/8" 32# J-55 LT&C casing set 4204'. Guide shoe set 4204', float collar set 4160'. Cemented w/1250 sx Halliburton Lite w/1/4# Flocele and 8# Salt (yield 1.84, wt 12.7). Tailed in w/200 sx Class C w/2% CaCl2 (yield 1.32, wt 14.8). PD 6:45 AM 10-7-89. Bumped plug to 2000 psi, float held okay. Cement circulated 45 sacks. WOC. Drilled out 9:00 AM 10-8-89. WOC 26 hrs and 15 minutes. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 10-10-89
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-147

(This space for State Use)
ORIGINAL SIGNED BY JERRY SEXTON
APPROVED BY DISTRICT I SUPERVISOR TITLE DATE OCT 12 1989
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

OCT 11 1989

**OCD
HOBBS OFFICE**