

Well Profile

=====

Measured Depth	True Vert Depth	Inclin. Degrees	Azimuth Degrees	Bearings Degrees	Rectangular Coordinates	Vertical Section
=====	=====	=====	=====	=====	=====	=====
5075.00	5074.63	1.00	326.00	N34.00W	19.13N	18.59E
5088.00	5087.63	0.75	325.00	N35.00W	19.29N	-19.29
5129.00	5128.63	0.75	250.00	S70.00W	19.42N	-19.42
5178.00	5177.62	1.50	209.00	S29.00W	18.75N	-18.75
5266.00	5265.59	1.50	181.00	S 1.00W	16.59N	-16.59
5359.00	5358.54	2.00	186.00	S 6.00W	13.76N	-13.76
5452.00	5451.48	2.25	194.00	S14.00W	10.38N	-10.38
5546.00	5545.40	2.50	201.00	S21.00W	6.67N	-6.67
5641.00	5640.32	2.25	201.00	S21.00W	3.00N	-3.00
5735.00	5734.25	2.00	201.00	S21.00W	0.26S	0.26
5940.00	5939.13	2.00	193.00	S13.00W	7.08S	10.15E
6127.00	6126.03	1.75	182.00	S 2.00W	13.12S	9.32E
6310.00	6308.98	1.00	193.00	S13.00W	17.46S	8.86E
6668.00	6666.92	1.00	208.00	S28.00W	23.27S	6.69E
6818.00	6816.90	1.00	223.00	S43.00W	25.38S	5.18E
7008.00	7006.87	1.00	234.00	S54.00W	27.57S	2.71E
7195.00	7193.81	2.00	273.00	N87.00W	28.36S	1.87W
7321.00	7319.69	3.00	286.00	N74.00W	27.33S	7.23W
7570.00	7568.07	5.00	295.00	N65.00W	20.95S	23.33W
7600.00	7597.97	4.41	293.80	N66.20W	19.93S	25.57W
7650.00	7647.85	3.43	290.88	N69.12W	18.62S	28.73W
7700.00	7697.79	2.46	285.66	N74.34W	17.80S	31.16W
7750.00	7747.75	1.54	274.00	N86.00W	17.46S	32.86W
7800.00	7797.74	0.84	237.71	S57.71W	17.61S	33.85W
7850.00	7847.74	1.01	173.15	S 6.85E	18.25S	34.10W
7900.00	7897.72	1.83	148.64	S31.36E	19.37S	33.64W
7950.00	7947.68	2.77	139.91	S40.09E	20.97S	32.44W
8000.00	7997.60	3.74	135.65	S44.35E	23.06S	30.53W
8050.00	8047.46	4.72	133.15	S46.83E	25.64S	27.83W
8100.00	8097.26	5.71	131.52	S48.48E	28.69S	24.52W

TIE POSITION