

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			Northwestern New Mexico		
Rustler					
T. Anhy	1806		T. Canyon		T. Penn. "B"
T. Salt			T. Strawn		T. Penn. "C"
B. Salt			T. Atoka		T. Penn. "D"
T. Yates	2442		T. Miss		T. Leadville
T. 7 Rivers			T. Devonian		T. Madison
T. Queen			T. Silurian		T. Elbert
T. Grayburg			T. Montoya		T. McCracken
T. San Andres	3720		T. Simpson		T. Ignacio Otzte
T. Glorieta	5080		T. McKee		T. Granite
T. Paddock			T. Ellenburger		T.
T. Blinebry			T. Gr. Wash		T.
T. Tubb	6542		T. Delaware Sand		T.
T. Drinkard			T. Bone Springs		T.
T. Abo	7382		T. Bough A	9150	T.
T. Wolfcamp	8582		T. Bough C	9248	T.
T. Penn			T.		T.
T. Cisco (Bough C)			T.		T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
 No. 2, from.....to.....
 No. 3, from.....to.....
 No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	40	40	Surface, Rock				
40	1183	1143	Redbeds				
1183	2000	817	Anhy, Redbeds				
2000	2400	400	Anhy,Cht, LM, Dolo,Sd,Sh				
2400	2600	200	SS, Anhy, Cht, Sh, LS				
2600	2840	240	Anhy,Cht,Dolo,Sd,Sh, LM				
2840	3100	260	Anhy, Dolo, Sd, Sh				
3100	3280	180	Anhy, Dolo, Sh,				
3280	3560	280	Anhy, Dolo, Sd, Sh, Cht				
3560	3720	160	Sh, Anhy,Dolo, Sd, Cht				
3720	4460	740	Dolo, Anhy, Sd				
4460	4570	110	LM, Dolo, Sh				
4570	4940	370	LM, Sh				
4940	7010	2070	Anhy, LS, Dolo, Sd, Sh				
7010	7310	300	Dolo, Anhy, Sd, Sh				
7310	7700	390	Sh, Dolo, Anhy				
7700	8440	740	Sh, Anhy, Dolo, Tr Sd				
8440	8770	330	Dolo, LS, Cht, Sh				
8770	9188	418	LS, Cht, Sh				
9188	9590	402	LS, Sh				