

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-30748
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-2722
7. Lease Name or Unit Agreement Name Remuda State Unit
8. Well No. 1
9. Pool name or Wildcat Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	
4. Well Location Unit Letter <u>H</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>East</u> Line Section <u>8</u> Township <u>10S</u> Range <u>33E</u> NMPM <u>Lea</u> County <u></u>	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) <u>4202' GR</u>	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Plugback, run production csg, perforate & treat

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 9590'. Reached TD 10:15 PM 2-2-90. Verbal permission given by Jerry Sexton, NMOCD, Hobbs, NM to Tim Bussell, YPC, to plug back well as follows:
Plug #1 9200' w/40 sx Class H
Plug #2 8632' w/40 sx Class H
Plug #3 7532' w/35 sx Class C
Plug #4 6592' w/45 sx Class C
Plug #5 4800' w/50 sx Class C. WOC 6 hrs. WIH, tagged cement @4588'. Drilled cement to 4640'. PBSD 4640'. Ran 111 jts 5 1/2" 15.5# J-55 LT&C casing set 4640'. Guide shoe set 4640', float collar set 4609'. Cemented w/500 gal WMW-1, 500 gal Surebond, 250 sx Class C w/.5% CF-1 (yield 1.32, wt 14.8). PD 11:30 AM 2-6-90. Bumped plug to 1000 psi for 3 mins, float and casing held okay. WOC 18 hrs. Perforated 4412-4447' w/20 - .42" holes as follows: 4412, 13, 14, 15, 16, 20, 21, 22, 31, 32, 33, 34, 38, 39, 40, 43, 44, 45, 46, and 4447'. Treated perforations w/3000 gals 20% NEFE acid.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 2-20-90
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY JERRY SEXTON TITLE DISTRICT SUPERVISOR DATE FEB 22 1990
CONDITIONS OF APPROVAL, IF ANY: