

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-31393
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	V-2522
7. Lease Name or Unit Agreement Name	FOX "A" STATE
8. Well No.	5
9. Pool name or Wildcat	ALLISON

10. Elevation (Show whether DF, RKB, RT, GR, etc.)	4055.6
--	--------

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator LAYTON ENTERPRISES, INC.
3. Address of Operator 3103 79 th ST. LUBBOCK, TX. 79423	4. Well Location Unit Letter F : 2310 Feet From The NORTH Line and 2070 Feet From The WEST Line Section 2 Township 9S Range 36E NMPM LEA County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4055.6	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

DRILLED TO TD 12,483 FT - RAN 5 1/2" 23# & 20#
N-80 CASING TO TD & CEMENTED W/ 500 SX.
CLASS H-FOAMIX PLUS 1500 SX HALLIBURTON LITE.
BUMPED PLUGS & TESTED TO 2000 PSI - HELD OK
RELEASED PRESSURE & FLOAT HELD - PRESSURE TO 1000 & CLOSE IN
INTEND TO RUN POROSITY LOGS - PERFORATE & TEST FOR
PRODUCTIVE INTERVALS.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Donald R. Layton TITLE PRESIDENT DATE 9-26-91
TYPE OR PRINT NAME DONALD R. LAYTON TELEPHONE NO. 806/745-7638

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE SEP 01 1991

CONDITIONS OF APPROVAL, IF ANY: