

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-31381
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	E-26; O.G.-1402 & V-2992

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: designation pending
OIL WELL ☐ GAS WELL ☐ OTHER production test

2. Name of Operator
LBO New Mexico, Inc.

3. Address of Operator
28202 Cabot Road, Suite 250, Laguna Niguel, CA 92677

4. Well Location
Unit Letter L : 1980 Feet From The South Line and 660 Feet From The West Line

Section 9 Township 11 S Range 33 E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- The well was spudded on 10/15/91 and a 17 1/4 hole was drilled to 367 feet at which depth 367 feet of 13 3/8 48 lbs. surface was set and cemented to surface with 350 sacks halliburton premium plus 2% call. WOC 27 1/2 hrs. test to 500 # for 30 min. held OK
- Drilled 11 inch hole to 3818' and set 1622' of 8 5/8 32 lbs. and 2196' of 24 lbs. intermediate casing. Cemented with 900 sacks haliburton premium plus 3% econo light with 200 sacks of premium plus neat cement. Ran temp. survey. Cement top at 975 feet.
- Drilled 7 7/8' hole to TD at 11,000 feet and set 10,948 feet of 5 1/2' casing N80 20 lbs. and 17 lbs. Cemented to surface.

Additional information to follow on C-105

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Raymond A. Diaz TITLE President DATE 12/02/91
TYPE OR PRINT NAME TELEPHONE NO.

(This space for State Use) ORIGINAL RECORD - DISTRICT OFFICE

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: