

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 30-025-31943
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-3322
7. Lease Name or Unit Agreement Name Simanola AMX State
8. Well No. 1
9. Pool name or Wildcat Southeast Lane Abo
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4197' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter <u>K</u> : <u>2310</u> Feet From The <u>South</u> Line and <u>1830</u> Feet From The <u>West</u> Line Section <u>15</u> Township <u>10S</u> Range <u>34E</u> NMPM Lea County
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Spud & surface casing <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17-1/2" hole at 5:00 PM 7-3-93. Drilled to 402'. Ran 10 joints of 13-3/8" 54.5# J-55 (402') of casing set at 402'. 1-Texas Pattern notched guide shoe set at 402'. Insert float set at 358'. Cemented with 200 sacks Class "C", 1/4#/sack celloseal and 2% CaCl2 (yield 1.33, weight 14.8). Tailed in with 200 sacks Class "C" 2% CaCl2 (yield 1.33, weight 14.8). PD 4:30 AM 7-4-93. Bumped plug to 600 psi, OK. Circulated 75 sacks cement. WOC. Drilled out at 12:30 AM 7-5-93. WOC 20 hours. Nippled up and tested to 600# for 30 minutes. Reduced hole to 11". Resumed drilling. NOTE: Notified NMOCD in Hobbs of spud and casing, no witness.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE August 5, 1993
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ DATE AUG 09 1993

CONDITIONS OF APPROVAL, IF ANY: