

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

U.S. CONS. COMMISSION
APPROVED
BUDGET BUREAU NO. 1004-0135
EXPIRES: MARCH 31, 1993
NEW MEXICO 88240

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

MARALO, INC.

3. Address and Telephone No.

P. O. BOX 832, MIDLAND, TX 79702

(915) 684-7441

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL & 990' FEL, SEC. 20, T9S, R35E, UNIT A

5. Lease Designation and Serial No.

NM 83101

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

S.L. FEDERAL "20" #1

9. API Well No.

30-025-32289

10. Field and Pool, or Exploratory Area

JENKINS, NE DEVONIAN

11. County or Parish, State

LEA, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other **COMMENCE DRILLING OPERATIONS**
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)


13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/04/94 SPUD WELL

12/05/94 RU & RAN 11 JTS 13-3/8" 48# CSG. SET @ 474'. CEMENTED 13-3/8" CSG W/450 SXS CLASS "C" CENT W/2% CACL₂. CEMENT CIRCULATED TO SURFACE. 9 HRS. MOC & NU BOP.

12/10/94 RU & RAN 108 JTS. 32# 8-5/8" CSG. SET @ 4200'. CEMENTED 8-5/8" CSG W/1300 SXS HALCO LIGHT CENT W/ 15# SALT PER SX + 250 SXS PREMIUM CENT W/2% CACL₂. CEMENT CIRCULATED TO SURFACE. 12 HRS. MOC & NU BOP.

12/11/94 THROUGH 12/18/94: DRILLING TO 8485'.



RECEIVED
DEC 20 11 00 AM '94
OFFICE OF THE
ATTORNEY GENERAL

14. I hereby certify that the foregoing is true and correct

Signed

Donna L. Began

Title **REGULATORY ANALYST**

Date **12/19/94**

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: