State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

to Appropriate
District Office

OIL	CONSER	VA	TION	DIVISION

P.O. Box 1980, Hobbs, NM \$8240	88 DIADIAI21014	WELL API NO. 30-025-332	25					
DISTRICT II P.O. Drawer DD, Anesia, NM \$8210	STRICT II Santa Fe, New Mexico D. Drawer DD, Ariesia, NM \$8210		5. Indicate Type of Lease					
DISTRICT III			STATE X FEE					
1000 Rio Brazos Rd., Aztec, NM 87410		VA-0333						
SUNDRY NOTICES								
(DO NOT USE THIS FORM FOR PROPOS. DIFFERENT RESERVOIR	L USE "APPLICATION FOR PE	RMIT	7. Lessa Name or Unit /	Igreement Name				
(FORM C-101)	FOR SUCH PROPOSALS.)							
OR. X WELL C	Shell State							
2. Name of Operator	505/623-1996		B. Well No.					
Manzano Oil Corporation 1. Address of Operator	1-Y 9. Pool name or Wildest							
P.O. Box 2107/Roswell, N	Cuerno Largo-Penn							
Well Location Unit Letter B: 330 F	ing From The North	Line and 226	O Feet From The	East line				
			1					
Section 26 1	owaship 10 South Ra		имрм Lea	Coucly				
		97 ' GL						
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data								
NOTICE OF INTENT	SEQUENT REPORT OF:							
PERFORM REMEDIAL WORK	ALTE	RING CASING						
TEMPORARILY ABANDON	OPNS. X PLUG	AND ABANDONMENT						
PULL OR ALTER CASING	меит рок тизм							
OTHER:		OTHER:						
12. Describe Proposed or Completed Operations (C	learly state all persinent details, an	d give pertinent dates, includ	ing emissand date of etartin	в олу ргорозе й				
1/22/96 Spud well 6:00	n.m. 1/21/96. Ran	10 its 13-3/8"_4	8# H40 csa. Se	t @ 404'KB.				
Cemented w/370 sks Cl C + 2% CaCl. Circl 150 sks.								
1/28/96 TD 3750'. Ran & cemented 8-5/8" 24 & 32# K55 ST&C csg w/6 centrilizers. Set @ 3750'. Cemented w/1100 sks of Pace Setter Lite w/5# salt per sks & 1/4# Floseal								
per sk. Tail i	n w/200 sks Cl C w/2	2% CaCl. Circul	ated 300 sks to	pit.				
2/19/96 TD 9150'. Relea	per sk. Tail in w/200 sks Cl C w/2% CaCl. Circulated 300 sks to pit. 2/19/96 TD 9150'. Released rig 5:00 a.m. 2/19/96. Ran & cemented <u>5-1/2"</u> 17# N80. Set @							
9150'. Cemented w/400 sks Pacesetter Lite. Tail in w/200 sks Cl H. Good returns throughout job. Pressure well to 1600 psi - OK.								
Tetat no tim ough	July Jobi Tressure	Mar. 00 2000 ps.						
I horsely carefy that the saformation above is true and con	npiete to the best of my knowledge and	belief.						
SIGNATURE allegation tours	echnician	TE 3/07/96						
TYPE ON PRINT NAME Allison Herna	ndez		TE	елионе на 623-1996				
Character Sup Hel								
OXICHNAL SIGNE	D BY JERBY SEXTON SUPERVISOR			MAR 13 1996				
DISTRIC!		1	DA'	TE				

APPROVED BY ---