

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

WELL API NO. 30-025-33350
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 18735

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Cobra Oil & Gas Corporation

3. Address of Operator

P.O. Box 8206 Wichita Falls, Texas 76307-8206

4. Well Location

Unit Letter M : 675 Feet From The South Line and 114 Feet From The West Line

Section 3 Township 10S Range 36E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4023' Gr

7. Lease Name or Unit Agreement Name

Lewis Unit

8. Well No.

1

9. Pool name or Wildcat

Wildcat Scissorsroads Dev.

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drill 8 3/4" hole to total depth of 12,284' (loggers), 12,269' (driller). Ran DST over interval from 12,155'-12,269' (driller). Ran open hole logs. Ran 5 1/2", 17# & 20# L-80, LT & C casing. Casing set @ 12,255' (driller), 12,270' (logger). Cemented csg w/450 sx Premium with .4% CFR-3 and .6% Halad-9 with 3.5#/sx salt, mixed @ 15.6 ppg, 1.22 cu ft/sx yield. Plug down at 7:20 AM, 6/13/96. Used 2 Weatherford Double Rev Bow Centralizers per joint on joints 1-10. Rig released at 2:30 PM, 6/13/96.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rory Edwards TITLE Production Supervisor DATE 6/14/96

TYPE OR PRINT NAME Rory Edwards TELEPHONE NO. (817) 716-5100

(This space for State Use)

JUN 21 1996

APPROVED BY ORIGINAL SIGNED BY JERRY ORTIZ TITLE DISTRICT SUPERVISOR DATE
CONDITIONS OF APPROVAL, IF ANY:

200 1 2 4 1

