Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobba, NM 88240 P.O. Box 2088	WELL API NO.
DISTRICT II Santa Fe. New Mexico 87504-2088	30-025-33755
P.O. Drawer DD, Artesia, NM 88210	5. Indicate Type of Lease STATE X FEE
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil & Gas Lease No.
	VA-0492
SUNDRY NOTICES AND REPORTS ON WELLS	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name
1. Type of Well: OIL. GAS WELL X WELL OTHER	Sawyer AQN State
2. Name of Operator YATES PETROLEUM CORPORATION	8. Well No.
3. Address of Operator	9. Pool name or Wildcat
105 South 4th St., Artesia, NM 88210	Sawyer San Andres, West
4. Well Location	
Unit Letter A: 810 Feet From The North Line and	Feet From The East Line
Section 6 Township 10S Range 37E	NMPM Lea County
Section 6 Township 105 Kange 37E	\(\lambda \) \(\la
//////////////////////////////////////	<u> </u>
11. Check Appropriate Box to Indicate Nature of Notice,	
NOTICE OF INTENTION TO:	JBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILL	ING OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING CASING TEST AND	
OTHER: OTHER: Frac pe	erforations X
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, in	acluding estimated date of starting any proposed
work) SEE RULE 1103. 3-16-17-97 - Opened well and flowed well down. Swabbed.	Shut well in.
3-18-97 - Opened well up and flowed well down. Swabbed.	Nippled down wellhead and
nippled up ROP Released packer. TOOH with tubing and	packer. Frac'd perforations
4000-4054! down casing with 21900 gallons $20%$ crosslink	gel & 50000# 16-30 sand, well
screened out with 2000# sand in formation. Flowed well	down. Till with tubing and
notched collar. Tagged sand at 4581' and circulated san	d to 502/'. Took with tubing
and notched collar. TIH with packer and tubing. Set pa	CKET At 4044 . 00_405%! with 20 025 gallons
3-19-97 - Pumped 50 bbls 2% KCL. Frac'd perforations 49 30# crosslink gel, 14250# 20-40 Brady sand and 33250# 16	-30 Brady sand Shut Well in
for 3 hours. Opened well up and flowed well down. Nipp	led down wellhead. Nippled up
BOP. Released packer. TOOH with packer and tubing. TI	H with tubing and tagged sand at
4970'. Washed sand down to 5027' (PBTD). TOOH with tub	ing. TIH with 7 joints of 2-3/8"
tubing, seating nipple, tubing anchor and 2-7/8" tubing.	Set seating nipple at 4586' and
tubing anchor at 4525'. Nippled down BOP. Nippled up w	ellhead. Prep to swab.
I hereby carrify that the information above is tree and complete to the best of my knowledge and belief.	CONTINUED ON NEXT PAGE:
SIGNATURE Kusty Vun mne Operations	Technician March 25, 1997
Rusty Klain	TELEPHONE NO. 505/748-147
TTPBOKPRUNI NAME	
(This space for State Use) ORIGINAL STOPED BY JERRY SEXTON	
ORIGINAL PROTECT I SUPERVISOR	MAR 2 6 11 17



YATES PETROLEUM CORPORATION Sawyer AQN State #2 Section 6-T10S-R37E Lea County, New Mexico

SUNDRY NOTICE CONTINUED:

3-20-97 - Swabbing.

3-21-97 - Swabbing.

3-22-24-97 - Swabbed. Shut well in. Released well to production department.

Rusky Klein

Operations Technician

March 25, 1997