## Submit 3 Copies to Appropriate District Office

## State of New Mexico Emergy, Minerals and Natural Resources Department

Form C-103

CONDITIONS OF APPROVAL,  $\mu \nu$  any:

OIL CONSERVATION DIVISION

Revised 1-1-89

TD 2995'. Reached TD at 7:30 PM 10-9-97. Ran of casing set at 2995'. 1-regular guide shoe so Cemented with 1000 sacks Class C (65-35-6), 5#/ (yield 2.04, weight 12.51). Tailed in with 200 weight 14.8). PD 3:00 PM 10-10-97. Bumped plu WOC. Nippled up and tested to 1000# for 15 min WOC 22 hours. Reduced hole to 7-7/8". Resumed	sack salt, and 1/4#/sack certoflake sacks Class C and 2% CaCl2 (yield 1.33, g to 1550 psi, OK. Circulated 96 sacks. utes, OK. Drilled out at 1:00 PM 10-11-97
TD 2995'. Reached TD at 7:30 PM 10-9-97. Ran of casing set at 2995'. 1-regular guide shoe so Cemented with 1000 sacks Class C (65-35-6), 5#/ (yield 2.04, weight 12.51). Tailed in with 200 weight 14.8). PD 3:00 PM 10-10-97. Bumped plu WOC. Nippled up and tested to 1000# for 15 min WOC 22 hours. Reduced hole to 7-7/8". Resumed	sack salt, and 1/4#/sack certofface sacks Class C and 2% CaCl2 (yield 1.33, g to 1550 psi, OK. Circulated 96 sacks. utes, OK. Drilled out at 1:00 PM 10-11-97 drilling.  Operations Technician  DATE Oct. 14, 1997
TD 2995'. Reached TD at 7:30 PM 10-9-97. Ran of casing set at 2995'. 1-regular guide shoe so Cemented with 1000 sacks Class C (65-35-6), 5#/ (yield 2.04, weight 12.51). Tailed in with 200 weight 14.8). PD 3:00 PM 10-10-97. Bumped plu WOC. Nippled up and tested to 1000# for 15 min WOC 22 hours. Reduced hole to 7-7/8". Resumed	sack salt, and 1/4#/sack certoflake sacks Class C and 2% CaCl2 (yield 1.33, g to 1550 psi, OK. Circulated 96 sacks. utes, OK. Drilled out at 1:00 PM 10-11-97
TD 2995'. Reached TD at 7:30 PM 10-9-97. Ran of casing set at 2995'. 1-regular guide shoe so Cemented with 1000 sacks Class C (65-35-6), 5#/ (yield 2.04, weight 12.51). Tailed in with 200 weight 14.8). PD 3:00 PM 10-10-97. Bumped plu WOC. Nippled up and tested to 1000# for 15 min	sack salt, and 1/4#/sack certoflake sacks Class C and 2% CaCl2 (yield 1.33, g to 1550 psi, OK. Circulated 96 sacks. utes, OK. Drilled out at 1:00 PM 10-11-97
TD 2995'. Reached TD at 7:30 PM 10-9-97. Ran of casing set at 2995'. 1-regular guide shoe so Cemented with 1000 sacks Class C (65-35-6), 5#/ (yield 2.04, weight 12.51). Tailed in with 200 weight 14.8). PD 3:00 PM 10-10-97. Bumped plu WOC. Nippled up and tested to 1000# for 15 min	sack salt, and 1/4#/sack certoflake sacks Class C and 2% CaCl2 (yield 1.33, g to 1550 psi, OK. Circulated 96 sacks. utes, OK. Drilled out at 1:00 PM 10-11-97
TD 00051 Prost TD 04 7.30 PM 10-9-97 Ran	- 2005! Float collar set at 2950'.
12. Describe Proposed or Completed Operations (Clearly state all persinent details, and give work) SEE RULE 1103.	68 joints of 8-5/8" 32# J-55 (2998.09')
· · · · · · · · · · · · · · · · · · ·	ER: Intermediate casing & cement X
	ING TEST AND CEMENT JOB
	IMENCE DRILLING OPNS. PLUG AND ABANDONMENT
	EDIAL WORK ALTERING CASING
Check Appropriate Box to Indicate Nature NOTICE OF INTENTION TO:	e of Notice, Report, or Other Data SUBSEQUENT REPORT OF:
Section 2 Township 10S Range 10. Elevation (Show whether DF, RK 4230' GR	<u> </u>
4. Well Location  Unit Letter P: 330 Feet From The South	Line and 330 Feet From The East Line
105 South 4th St., Artesia, NM 88210	Mescalero Cisco Northeast
YATES PETROLEUM CORPORATION  3. Address of Operator	9. Pool name or Wildcat
OB. WELL X OTHER  2. Name of Operator	Mescalero ARL State 8. Well No.
SUNDRY NOTICES AND REPORTS ON WELLS  ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLI DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (FORM C-101) FOR SUCH PROPOSALS.)  1. Type of Well:	
	6. State Oil & Gas Lease No.  VA-0621
1000 Rio Brazos Rd., Aztec, NM 87410	STATE X FEE
DISTRICT II Santa Fe, New Mexico 87504 P.O. Drawer DD, Artesia, NM 88210  DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	5. Indicate Type of Lease

