Form 3160-5 (June 1990)	DEPAL _/	NITED STATES ENT OF THE INTERIOR F LAND MANAGEMENT	Hoddes, NM 88241	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS				NRT CO(FO)
Do not use this form for proposals to drill or to depend				NMLC065249 6. If Indian. Allottee or Tribe Name
	Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals			
1. Type of Weil				
2. Name of Operator	2. Name of Operator			
Reliance 3. Address and Telep	Reliance Operating Company 3. Address and Telephone No.			
				9. API Well No. 30-025-34066
4. Location of Well (P 0 Box 10946, Midland TX 79702 915-683-4816 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 915-683-4816			
Unit O, Se	ection 31, T9S, R36 & 1420' FEL	Description)		10. Field and Pool, or Exploratory Area Crossroads Devonian West 11. County or Parish, State
IZ. CHEC	CK APPROPRIATE BOX			Lea
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT				T, OR OTHER DATA
		TYPE OF ACTION		
Subsequent Report		Abandonment		
		Recompletion		Change of Plans
200. Lab	sequent Report	Plugging Back		New Construction
E:		Casing Repair		Won-Routine Fracturing
13. Describe Proposed of Computer Occurry Classification		Altering Casing		Conversion to Injection
				Dispose Water
give subsurface	locations and measured and true vertice	pertinent details, and give pertinent dates al depths for all markers and zones perti	s. including estimated date of starting an	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) ny proposed work. If well is directionally drilled,
8/19/97	Spud well @ 2:45 PM. Ran 10 jts 13 3/8" 54.5# csg (444.89'). Set & cmt @ 422' KB w/240 sx Halliburton CZ w/2 1b/sk flowseal. Tail w/120 sx PP w/0.2% CaCl2. Plug down @ 1:50 AM 8/20/97. Circulate 57 sx.			
8/29/97	Ran 106 jts 8 5/8" 32# K55 csg @ 4496' Circ & cmt w/1300 sx HCL PP, 8 1b/sk, 1/4#/sk flocele, 250 sx PP 1% CC.			
10/2/97	Reached TD of 12,018'.			
10/7/97	Ran 276 jts 17 & 20# 5 1/2" csg w/inflatable guide shoe, 30 centralizers & 2 cmt baskets. Set in cmt @ 12,003' KB w/400 sx Prem 50/50 Poz 2% gel .4% CFR-3 + .4% Halad 9, 1/4# flocele 5#/sk microbard 1#/sk gelsonite .1% HR-7. Plug down 12 PM 10/7/97. Released rig @ 2 PM 10/7/97.			
4. I hereby certify that the Signed	foregoing is true and correct			
(This space for Federal of		Title Agent		Date <u>11/4/97</u>
	State Office Use)		100 053020	
Approved by Conditions of approval.	if any:	Title	SANTON GLAR	Date
itle 18 U.S.C. Service 1001	maka	XOV 1		
representations as to any m	atter within its jurisdiction.	vingly and willfully to make to any depa	runent or agency of the United States	any false, fictitious or fraudulent statements

*See Instruction on Reverse Side