

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-34790
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	VA-1314
7. Lease Name or Unit Agreement Name	East Sand Springs Unit
8. Well No.	1
9. Pool name or Wildcat	Sand Springs Atoka Morrow

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter L : 1000 Feet From The North Line and 660 Feet From The West Line Section 5 Township 11S Range 35E NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4155' GR	

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
11. NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Production casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 12455'. Reached TD at 11:15 PM 2-2-2000. Ran 298 joints of 4-1/2" 11.6# HCP-110 (12462.86') of casing set at 12455'. Float shoe set at 12455'. Float collar set at 12412'. Bottom marker set at 11552'. Cemented with 1660 sacks "C" (61-15-11), .9% FL50, .5% CD-32 and 5#/sack gilsonite (yield 1.64, weight 13.0). PD 11:10 PM 2-3-2000. Bumped plug to 2800 psi for 3 minutes, OK. WOC. Released rig at 5:00 AM 2-4-2000. NOTE: Notified Sylvia w/OCD-Hobbs of intent to set and cement production casing.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Operations Technician

DATE

April 15, 2000

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: