


SURVEY CERTIFICATION

State of Texas

County of MIDLAND

I, Douglas R. Gage certify that; I am employed by Dailey International Inc.;
that I did on the day(s) of 8/12 through 8/30 conduct or supervise the
taking of a Steering tool survey from a depth of 13000 feet to a depth of
14201 feet; the data is true, correct, complete, and within the limitations of
the tool as set forth by Dailey International Inc.; that I am authorized and qualified
to make this report; that this survey was conducted at the request of Vites
Retroleum for the Blitzow AUB Well API
No. State #2 in Lee County, Texas, and that I
have reviewed this report and find that it conforms to the principles and
procedures as set forth by Dailey International Inc.



30-025-34859
SUR: P-16-115-34
800/S & 850/E
BHL: I-16-115-34
1839/S & 344/E

Job Number: WTX0800D245
 Company: Yates Petroleum Corp.
 Lease/Well: Blitzen AUB State #2
 Location: Lea County
 Rig Name: Patterson #80
 RKB:
 G.L. or M.S.L.:

State/Country: New Mexico
 Declination:
 Grid:
 File name: C:\WINSERVE\YATES\BLITZEN\S.VY
 Date/Time: 30-Aug-00 / 13:43
 Curve Name: WORK

DAILEY INTERNATIONAL Inc.
 MIDLAND, TEXAS

WINSERVE SURVEY CALCULATIONS

Minimum Curvature Method

Vertical Section Plane 24.23

Vertical Section Referenced to offset from Wellhead: EW =.00 Ft, NS=.00 Ft

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE Distance FT	Direction Deg	Dogleg Severity Deg/100	BUILD RATE Deg/100
TIE-IN FIGYRO SURVEY										
12970.00	.20	347.16	12968.60	-17.03	79.73	17.19	81.53	102.06	.00	.00
12985.00	1.40	53.00	12993.60	-16.80	79.96	17.49	81.71	101.87	5.32	4.80
13000.00	2.00	53.00	12998.60	-16.71	80.08	17.62	81.81	101.79	12.00	12.00
13005.00	3.30	39.50	13003.59	-16.55	80.24	17.84	81.93	101.65	28.67	28.00
1ST SURVEY W/ STEERING TOOL										
13010.00	7.30	23.60	13008.57	-16.15	80.46	18.30	82.07	101.35	84.47	80.00
13015.00	9.70	17.20	13013.51	-15.45	80.71	19.03	82.18	100.84	51.52	48.00
13020.00	12.00	13.70	13018.42	-14.55	80.96	19.96	82.26	100.19	47.83	46.00
13025.00	14.40	13.70	13023.29	-13.44	81.23	21.08	82.34	99.39	48.00	48.00
13030.00	17.60	17.00	13028.10	-12.11	81.60	22.45	82.49	98.44	66.51	64.00
13035.00	22.00	22.20	13032.80	-10.52	82.18	24.13	82.85	97.30	94.71	88.00
13040.00	25.40	24.70	13037.38	-8.68	82.98	26.14	83.43	95.97	70.89	68.00
13045.00	28.60	27.40	13041.83	-6.64	83.98	28.41	84.24	94.52	68.52	64.00
13050.00	31.90	29.40	13046.15	-4.43	85.18	30.92	85.29	92.98	69.00	66.00
13055.00	35.40	31.30	13050.31	-2.04	86.58	33.67	86.60	91.35	73.09	70.00
13060.00	39.10	32.40	13054.29	.53	88.18	36.67	88.18	89.65	75.19	74.00
13065.00	41.80	33.00	13058.10	3.26	89.93	39.87	89.98	87.93	50.60	50.00
13070.00	45.10	33.50	13061.74	6.13	91.81	43.26	92.01	86.18	70.34	70.00
13075.00	48.90	33.90	13065.15	9.17	93.84	46.87	94.28	84.42	76.22	76.00
13080.00	52.60	34.60	13068.31	12.37	96.02	50.68	96.81	82.66	74.79	74.00
13085.00	56.20	35.60	13071.22	15.69	98.35	54.67	99.60	80.94	73.81	72.00
13090.00	60.40	37.20	13073.85	19.11	100.88	58.83	102.67	79.27	88.30	84.00
13095.00	64.10	38.40	13076.17	22.61	103.59	63.13	106.03	77.69	76.99	74.00

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE Distance FT	Direction Deg	Dogleg Severity Deg/100	BUILD RATE Deg/100
14105.00	88.90	12.50	13070.89	943.84	487.00	1080.55	1082.07	27.29	3.12	-1.87
14137.00	88.90	11.50	13071.61	975.13	493.65	1091.82	1092.97	26.85	3.12	.00
14169.00	90.00	10.60	13071.81	1006.53	499.79	1122.98	1123.79	26.41	4.44	3.44
14201.00	89.80	9.40	13071.87	1038.05	505.34	1153.99	1154.52	25.96	3.80	-.03