

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-34860
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	V-5563
7. Lease Name or Unit Agreement Name	
Donner AUH State Com	
8. Well No.	1
9. Pool name or Wildcat	Wildcat Mississippian

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter A : 660 Feet From The North Line and 1000 Feet From The East Line Section 26 Township 11S Range 34E NMMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4148' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud, conductor, resume drilling, surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 1:45 PM 1-25-2000. Drilled to 40'. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified Sylvia w/OCD-Hobbs of intent to spud. Resumed drilling a 14-3/4" hole with rotary tools at 9:45 AM 1-27-2000.

TD 404'. Reached TD at 3:30 PM 1-27-2000. Ran 9 joints of 11-3/4" 42# H-40 (408.31') of casing set at 404'. 1-Texas Pattern notched guide shoe set at 404'. Insert float set at 374'. Cemented with 79 sacks "C" (65-35-6) and 2% CaCl2 (yield 1.87, weight 12.7). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 12:07 AM 1-28-2000. Cut off and welded on flow nipple. Drilled out at 8:15 PM 1-28-2000. WOC 20 hours and 5 minutes. Reduced hole to 11". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE April 7, 2000

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-147

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: