

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.

30-025-34898

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

V-1315

7. Lease Name or Unit Agreement Name:

East Sand Springs Unit

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

7. Well No.

#3

8. Pool name or Wildcat

Wildcat Mississippian

4. Well Location

Unit Letter **N** : **1000** feet from the **South** line and **1400** feet from the **West** line

Section **6** Township **11S** Range **35E** NMPM **Lea** County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

4182' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE
COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND
ABANDONMENT ☐

CASING TEST AND
CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion
or recompletion.

3/27/00 - Spudded at 9:30 AM with 26" conductor hole. Set 40' of 20" conductor.

12/14/00 - Move in and RU rotary tool.

12/15/00 - Resumed drilling at 11:00 PM with rotary tool.

12/16/00 - TD of 14-3/4" hole at 387'. Ran 9 jts (390.87') of 11-3/4" 42# H-40 ST&D casing set at 387'. Texas
Pattern notched guide shoe set at 387'. Insert float set at 342'. Cemented with 300 sxs "C" 2% CaCl₂ (yld 1.32,
wt 14.8). PD 12:45 AM. Bumped plug to 250 psi, held OK. Circ 45 sxs.

12/17/00 - Drilled out at 12:00 PM. WOC 35 1/4 hrs. Reduced hole to 11" and resumed drilling.

12/23/00 - TD 11" hole at 4142'. Verbal permission obtained from Chris with NM OCD.

Ran 100 jts 8-5/8" J55 32# casing set at 4142'. Float shoe set at 4140.50'. Float collar set at 4098.49'. Cemented
with 1100 sxs 35/65 Poz "C" with 5 pps salt, 1/4 pps celloflake (yld 2.08, wt 14.8) Tailed in 200 sxs "C" 2% CaCl₂ (yld
1.32, wt 14.8). PD 11:45 PM. Bumped plug to 1700 psi, held OK. Circ 105 sxs. Shut down for Holidays.

See Attached

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE  TITLE **Engineering Technician** DATE **August 29, 2001**

Type or print name **Susan Herpin**

Telephone No. **505-748-1471**

(This space for State use)

APPROVED BY _____ TITLE _____ DATE _____

Conditions of approval, if any: