

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-34899

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

VO-4510

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

7. Lease Name or Unit Agreement Name

Sand Springs ASU State

8. Well No.

4

9. Pool name or Wildcat

Sand Springs Devonian

4. Well Location

Unit Letter B : 700 Feet From The North Line and 1650 Feet From The East Line

Section 11

Township 11S

Range 34E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4146' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Intermediate casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4203'. Reached TD at 7:30 PM 2-23-2000. Ran 94 joints of of 9-5/8" 36# & 40# J-55 (4219.63') of casing set at 4178'. Float shoe set at 4178'. Float collar set at 4133'. Cemented with 975 sacks Interfill C, 1/4#/sack flocele and 5#/sack gilsonite (yield 2.62, weight 11.7). Tailed in with 250 sacks Premium Plus with 1% CaCl2 (yield 1.33, weight 14.8). PD 6:05 PM 2-23-2000. Bumped plug to 1450 psi, OK. Circulated 50 sacks. WOC. Nipped up and tested BOP to 5000 psi for 30 minutes, OK. Drilled out at 7:15 PM 2-24-2000. WOC 25 hours and 10 minutes. Reduced hole to 8-3/4". Resumed drilling.

NOTE: SLM - 4203' - 25' long - depth corrected prior to running casing

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Operations Technician

DATE March 24, 2000

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-147

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: